

电感模压成型机参数表

		单位(Unit)	H30	H60	H100	H150	H200	H250	
合模单元 CLAMPING UNIT	合模力Clamping Force	kN(tf)	294(30)	588(60)	980(100)	1176(120)	1960(200)	2450(250)	
	合模行程Clamping Stroke	mm	200	250	250	280	200	200	
	取小模厚MIN. MOLD Thickness	mm	200	245	245	245	280	280	
	最大開距Max. Daylight	mm	400	495	495	525	480	480	
	拉杆间距 (L*W) Distance Between Tie Bars	mm	370*210	500*385	500*385	605*385	660*410	660*410	
	頂出行程Ejector Stroke	mm	100	100	100	100	100	100	
	頂出力Ejector Force	tf	5	10	10	10	15	15	
拉力 Pulling Force		4	9	9	9	13	13		
其他 OTHERS	系統壓力 System Pressure	Mpa(kgf/cm <sup>2</sup> )	16(165)	15.7(160)	15.7(160)	13.7(140)	16.2(165)	18.3(180)	
	油箱容量 Oil Tank Capacity	L	70	80	220	220	250	250	
	电机功率 Motor Power	kW	5.5	9	15	18	32	32	
	機械尺寸 Machine Dimension	L*W	mm	1340*865	1645*1176	2000*1250	2000*1360	1767*1638	1767*1638
		H	mm	2115	2354	2520	2720	2612	2697
機械重量 Machine Weight	ton	1.1	1.8	3	3.2	5.5	6		